

Serial No. 10/607,899

In the Claims:

1. (Original) An apparatus comprising:  
a VCSEL (vertical cavity surface emitting laser) formed on a top surface of a substrate that is transmissive to light emitted by the VCSEL;  
a photodetector disposed facing an opposed bottom surface of the substrate and capable of detecting light emitted by the VCSEL; and  
an angular filter disposed between the bottom surface and a detecting surface of the photodetector and capable of allowing only light which reaches the angular filter within a limited range of angles, to reach the photodetector.
2. (Original) The apparatus as in claim 1, wherein the photodetector is disposed directly beneath the VCSEL.
3. (Original) The apparatus as in claim 1, wherein the bottom surface is polished to reduce scattering of the light emitted by the VCSEL, within the substrate.
4. (Original) The apparatus as in claim 3, wherein an anti-reflective coating is formed on the polished bottom surface.
5. (Original) The apparatus as in claim 1, wherein the angular filter is formed of a multi-layered dielectric material.
6. (Original) The apparatus as in claim 1, wherein the angular filter is disposed one of on the bottom surface of the substrate and on the detecting surface of the photodetector.
7. (Original) The apparatus as in claim 1, wherein the VCSEL is coupled to an optical transmission medium to deliver an optical data signal.

Serial No. 10/607,899

8. (Original) The apparatus as in claim 1, wherein the VCSEL is included within an array of VCSELs formed on the top surface.
9. (Original) The apparatus as in claim 8, in which the angular filter prevents light emitted by other VCSELs of the array of VCSELs, from reaching the detecting surface of the photodetector.
10. (Original) The apparatus as in claim 8, further comprising adjusting means for adjusting optical output of a plurality of VCSELs of the array of VCSELs based on light detected by the photodetector.
11. (Original) The apparatus as in claim 1, in which the VCSEL is capable of emitting a primary light beam from the top surface and a secondary light beam through the substrate and exiting from the bottom surface, the photodetector capable of sensing the secondary light beam.
12. (Original) The apparatus as in claim 1, wherein the substrate comprises one of silicon and gallium arsenide.
13. (Original) The apparatus as in claim 1, wherein the angular filter is mounted one of on and within a further member disposed between the bottom surface of the substrate and the photodetector, portions of a top surface of the further member including an absorbing epoxy layer formed thereon and capable of absorbing light.
14. (Original) The apparatus as in claim 1, in which the angular filter prevents light which exits the bottom surface of the substrate at angles less than 45 degrees, from reaching the photodetector.
15. (Original) The apparatus as in claim 1, in which the angular filter includes a filter surface and wherein the limited range of angles comprise angles greater than 45 degrees with the filter surface.

Serial No. 10/607,899

16. (Original) The apparatus as in claim 1, further comprising adjusting means for adjusting optical output of the VCSEL based on light detected by the photodetector.

17-26 (Canceled)

27. (New) An apparatus comprising:

a VCSEL (vertical cavity surface emitting laser) formed on a top surface of a substrate that is transmissive to light emitted by the VCSEL;

a photodetector disposed facing an opposed bottom surface of the substrate and capable of detecting light emitted by the VCSEL; and

filter means disposed between the bottom surface and a detecting surface of the photodetector for allowing only light within a limited range of angles to reach the photodetector.

28. (New) The apparatus as in claim 27 wherein said filter means comprises:

an angular filter disposed between the bottom surface and a detecting surface of the photodetector,

said angular filter being configured and arranged to allow only light which reaches the angular filter within a limited range of angles to reach the photodetector

29 (New) The apparatus as in claim 28 wherein said photodetector is disposed directly beneath the VCSEL.

30. (New) The apparatus as in claim 28 wherein the VCSEL is included within an array of VCSELs formed on the top surface.

31. (New) The apparatus as in claim 30, in which the angular filter prevents light emitted by other VCSELs of the array of VCSELs, from reaching the detecting surface of the photodetector.

Serial No. 10/607,899

32. (New) The apparatus as in claim 30, further comprising adjusting means for adjusting optical output of a plurality of VCSELs of the array of VCSELs based on light detected by the photodetector.
33. (New) The apparatus as in claim 27 wherein said filter means comprises:  
an anti-reflective coating formed on the bottom surface of said substrate, said bottom surface being polished to reduce scattering of light emitted by the VCSEL.
34. (New) The apparatus as in claim 33, wherein the photodetector is disposed directly beneath the VCSEL.
35. (New) The apparatus as in claim 33, wherein the bottom surface is polished such that internal diffuse reflection is less than 1/100 of specular reflection.
36. (New) The apparatus as in claim 33, wherein the anti-reflective coating is selected from the group consisting of titanium oxide, tungsten oxide, silicon monoxide, silicon dioxide and magnesium fluoride.
37. (New) The apparatus as in claim 33, wherein the anti-reflective coating has a refractive index that is approximately the square-root of the refractive index of the substrate.
38. (New) The apparatus as in claim 33, wherein the VCSEL is included within an array of VCSELs formed on the top surface.
39. (New) The apparatus as in claim 33, in which the VCSEL is capable of emitting a primary light beam from the top surface and a secondary light beam through the substrate and exiting from the bottom surface, the photodetector capable of sensing the secondary light beam.

Serial No. 10/607,899

40. (New) The apparatus as in claim 33, wherein the substrate comprises one of silicon and gallium arsenide.

41. (New) The apparatus as in claim 33, further comprising an angular filter disposed between the bottom surface and a detecting surface of the photodetector and capable of allowing only light which reaches the angular filter within a limited range of angles to reach the photodetector.

42. (New) The apparatus as in claim 33, further comprising adjusting means for adjusting optical output of the VCSEL based on light detected by the photodetector.